



	Outlet Size	Dimensions			Weight
		A	B	C	
CLASS 3000	NPS ¼	¾	1 ⅛	0.437	0.140
	NPS ⅜	1 ⅜	1 ⅛	0.578	0.140
	NPS ½	1	1 ½	0.718	0.280
	NPS ¾	1 ⅛	1 ⅞	0.922	0.390
	NPS 1	1 ⅝	2 ½	1.156	0.730
	NPS 1 ¼	1 ⅝	2 ½	1.500	0.960
	NPS 1 ½	1 ¾	2 ⅞	1.734	1.120
	NPS 2	1 ½	3 ⅝	2.218	1.660
	NPS 2 ½	1 ⅞	3 ⅝	2.625	2.730
	NPS 3	2	4 ¾	3.250	3.880
NPS 4	2 ¼	5 ⅞	4.250	6.180	
CLASS 6000	NPS ¼	¾	1 ⅛	0.437	0.140
	NPS ⅜	1 ⅜	1 ⅝	0.578	0.140
	NPS ½	1 ¼	1 ¾	0.718	0.280
	NPS ¾	1 ⅞	2 ⅛	0.922	0.390
	NPS 1	1 ⅞	2 ⅞	1.156	0.730
	NPS 1 ¼	1 ¾	2 ½	1.500	0.960
	NPS 1 ½	1 ⅞	3 ⅝	1.734	1.120
	NPS 2	2 ⅛	4	2.218	1.660



RUN SIZE CONSOLIDATIONS - CLASS 3000											
Outlet Size											
	¼	⅜	½	¾	1	1 ¼	1 ½	2	2 ½	3	4
RUN SIZES	¾ - ¼	1 - ⅜	½	1 ¼ - ¾	1	1 ½ - 1 ¼	1 ½	2	2 ½	3	4
	36 - ½	36 - 1 ¼	36 - ¾	36 - 1 ½	2 ½ - 1 ¼	3 ½ - 2	2 ½ - 2	3 ½ - 2 ½	3 ½ - 2 ½	5 - 3 ½	6 - 5
					36 - 3	36 - 4	5 - 3	6 - 4	6 - 4	14 - 6	20 - 8
							36 - 6	36 - 8	36 - 8	36 - 16	36 - 22

▶ FLAT Flexolet branch connections for use on welding caps, elliptical heads, and flat surfaces is available upon request.

RUN SIZE CONSOLIDATIONS - CLASS 6000								
Outlet Size								
	¼	⅜	½	¾	1	1 ¼	1 ½	2
RUN SIZES	¾ - ¼	1 - ⅜	½	¾	1	1 ½ - 1 ¼	1 ½	2
	36 - ½	36 - 1 ¼	36 - ¾	1 ¼ - 1	2 ½ - 1 ¼	3 ½ - 2	2 ½ - 2	3 ½ - 2 ½
				36 - 1 ½	36 - 3	8 - 4	5 - 3	6 - 4
						36 - 10	36 - 6	36 - 8